







「Smart SMOTION」 Wave to stop wherever you like*

Control power and lighting instantly with a wave* Ascend for more spacious view, descend for efficient smoke extraction

 $^{^{*}}$ Tested for 50000 ascend-and-descend cycles, and continued to operate stably

^{*} Equipped with millisecond-level wave sensing technology for immediate response, no delay in control







Innovative and Humanized Design



Smart Sync

Range hood activates automatically with gas ignition



Filter-Free Design

Easy wipe to restore original shine



Hidden Oil Cup

Oil cup automatically hides when turn off



Colour Touch Panel

Seamless UI interface for ultimate user experience



Canopy-style Lighting


10W ultra-bright lighting for full area coverage




BI	G	9	0	5	9
	\sim	\sim	$\mathbf{\circ}$	\sim	$\overline{}$

Product Specification				
Certification	CB, SIRIM			
Power Supply	220-240V 50Hz			
Type of Motor	BLDC			
Motor Power (W)	450			
Illumination Power in LED (W)	10W			
Speed Setting	Turbo+2			
Max IEC Airflow (m³/h)	1530			
Max Unrestrained Airflow (m³/h)	2850			
Noise Level (dB)	47/39			
Max Static Pressure (Pa)	1240			
Delay Off	2min			
Control Type	Touch + Motion			
Filter	Filter Free			
Intelligent Elevation Adjustment	Υ			
Screen Lock	Υ			
Smart Sync	Υ			
Product Dimensions (WxDxH)	892 x 370 x 690			

Installation Diagram





Installation Guide:

- 1.The cabinet's effective width should be ≥900mm. Avoid adding side panels at the hinge. The gap between hood and cabinet should be ≥5mm on both sides.
- 2.The cabinet's internal height should be ≥750mm.
- - ②Cabinet depth (including door) 350mm to < 395mm: Suitable for raised mount installation. A 55mm gap at the bottom of the cabinet door is required for alignment with the hood.
 - ③Cabinet depth (including door) ≥395mm: Suitable for full integrated installation.
- 4. Position the power outlet in the top left or right corner to avoid obstruction by the hood.
- 5. The wall must have a hard surface, like ceramic tiles, to support the hood motor.
- 6.Ensure the distance between the cabinet door hinge and the bottom of cabinet is ≥65mm.
- 7.The distance between the bottom of cabinet and the door stopper should be ≥500mm.
- 8. With a 750±20mm installation height, the distance between the hood and countertop should be 350-390mm when the hood is at its lowest position.
- 9. The installation height can be adjusted based on user's height but should not exceed the recommended range. Installing too low may block the cooking view, while too high may reduce suction efficiency.